B2030P

Technical Specifications

Version 1.0 August 2003



TRUTH



www.behringer.com

TRUTH B2030P



▲ High-resolution, passive 2-way 100-Watt nearfield monitor

▲ Ultra-linear frequency response from 75 Hz to 21 kHz

Extremely high-resolution, ferrofluid-cooled tweeter

▲ Long-throw 6 ¾" woofer with special polypropylene diaphragm and deformation-resistant aluminum diecast chassis

Controlled dispersion characteristics and extremely large "sweet spot" through BEHRINGER's wave guide technology

A Phase-optimized, low-distortion frequency crossover for accurate reproduction

Magnetically shielded for placement near computer monitors

Delivered as "matched pairs"

Low-vibration, environment-friendly E1 MDF cabinet

Designed in Germany. Manufactured under ISO9000 certified management system

TRUTH B2030P

SPECIFICATIONS

CONNECTOR Type	binding posts
SYSTEM SPECIFICATIONS Load capacity Impedance Frequency response Sound pressure level	100 watts 8 Ω 75 Hz to 21 kHz 89 dB (1 W/1 m)
COMPONENTS Tweeter Woofer	¾" dome, ferrofluid-cooled 6 ¾" polypropylene diaphragm
CROSSOVER Crossover frequency	2.3 kHz
DIMENSIONS/WEIGHT Dimensions (H x W x D) Weight	12 1/2" (317 mm) x 8 2/5" (214 mm) x 8 3/10" (211 mm) 7.0 kg (15 1/3 lbs)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER is a registered trademark. ALL RIGHTS RESERVED. © 2003 BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany Tel. +49 2154 9206 0, Fax +49 2154 9206 4903